

ROASTER DU – GP1GC – R76



AVAILABLE COLORS



ACCESSORIES



CABINET OPTIONS



TECHNICAL INFORMATION

Productivity	± 135 Diners
Fire up time	30 min average
Charcoal daily consumption*	Charcoal 31 – 37 kg
Roasting temperature	250 °C to 350 °C
Exhaust rate	4.500 m3/h

DIMENSIONS & WEIGHTS

Dimensions (NET)	1785X825X1645 mm
Weight (NET)	595 kg

INSTALLATION

Clearance with non-flammable equipment	100 mm
Clearance with flammable equipment	300 mm

INCLUDED

Fire braker	Tong	Grill Scraper	2X Stainless Steel Grill Grates Oven
Clip Tong	Ash Shovel	1X Grill Grate Parrilla	2X Parrilla Upper Grill Rack
Thermal Protection	2x Top GN Trays	Wire Brush	Poker
Grease Collector	Ash Collector Drawer	Charcoal Starter	Packaging

TECHNICAL INFORMATION ROC76

Productivity + -	110 dinners
Roasting area	735X590 mm
Fire up time	30 min average
Charcoal daily consumption*	Charcoal 15 – 17 kg
Roasting temperature	250 °C to 350 °C
Exhaust rate	2.500 m3/h
Heat Output*	8 kw
Extraction diameter	180 mm
Performance*	9h
Dimensions without Packaging	985X825X1645 mm
Dimensions with Packaging	1130X1020X1930 mm
Net Weight	410 kg
Gross Weight	478kg



TECHNICAL INFORMATION GP1GC

Roasting area	630X620 mm
Fire up time	30 min average
Charcoal daily consumption*	Charcoal 16 – 20 kg
Grilling temperature	200 °C to 250 °C
Exhaust rate	2.000 m3/h
Dimensions without Packaging	800X825X1550 mm
Dimensions with Packaging	930X1020X1790 mm
Net Weight	185 kg
Gross Weight	261 kg




*Depends on the charcoal quality




TECHNICAL DRAWINGS


Front view




Side view




Dimensions with Open Door




Top view




Roasting area Oven



Roasting area Parrilla



MAIN COMPONENTS



*Dimensions in mm

*The charcoal multi is subject to technical and design changes without previous notice

